

Mild Solvent Printer



Item		Specification	
Model		TW-3306HC / 3306GB	
Printhead		Seiko Instrument Group SPT Printhead From In Japan	
Number of printhead		6 or 4Heads	6 or 4Heads
Number of Model		SPT-510/35pl	SPT-255/35pl
Print Speed*	printing mode	(Output)m ² /hr	(Output)m ² /hr
	240x540dpi 3pass	48.19m ² /hr	24.10m ² /hr
	240x720dpi 4pass	37.12m ² /hr	18.56m ² /hr
	240x540dpi 6pass	25.63m ² /hr	12.82m ² /hr
	360x540dpi 3pass	35.73m ² /hr	17.87m ² /hr
	360x720dpi 4pass	26.80m ² /hr	13.40m ² /hr
	360x540dpi 6pass	18.46m ² /hr	9.23m ² /hr
	360x720dpi 8pass	14.04m ² /hr	7.02m ² /hr
Maximum Print Width		3,200mm(125.984inch)	
Ink	Type	Solvent Ink	
	Color	(C,M,Y,K,L,C,LM) / (C,M,Y,K)	
	Capacity	5,000ml Per Main Tank of Each Color	
	Ink Supply System	Low Ink Detector,Auto or Manual Ink Supply System	
Media	Width	Maximum3,300mm	
	Type	Vinyl,Window Film,Polyester,Flex,Back-lit film,etc. Roll Media or Sheet Media	
Auto Media Feeding System		Equipped (80kg Max.Media Weight 80kg)	
Auto Cleaning System		Positive Cleaning	
		Anti-clogged Flash Function	
Pre-heat & Dry System		Equipped (Drying System Optional)	
Clamp		Equipped	
Print Interface		USB2.0	
Printhead High		4mm 2 to 4mm Above Media Adjustable	
Compatible RIP Software		Maintop , Photoprint , Ultraprint	
Input Power		AC220V,50Hz	
Machine Dimension		L4,450mm X W765/750mm X H1,305/1,350mm	
Package Dimension		L4,650mm X W950mm X H1,450/1,500mm	
Working Environment		Temperature 20℃-30℃	Humidity 40-60%